



02-14-05

2863

PATENT
Attorney Docket No. JP920000287US1
Express Mail Label No. EV332925782US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

Ajith Kumar NARAYANAN

Serial No: 10/010,104

Filed: November 8, 2001

SELECTING A TARGET DEVICE IN A DEVICE
NETWORK

Examiner: LE, John H.

Art Unit: 2863

BEST AVAILABLE COPY

SUBMISSION OF PRIORITY DOCUMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450


Dear Sir:

Enclosed please find Singapore Patent Application No. 200006973-2, the foreign priority for the above-identified patent application.

No fee is believed due with this Submission, however, should a fee be required please charge Deposit Account 50-0510. Should any extensions of time be required, please consider this a petition thereof and charge Deposit Account 50-0510 the required fee.

Respectfully submitted,

Dated: February 12, 2005


Ido Tuchman, Reg. No. 45,924
Law Office of Ido Tuchman
69-60 108th Street, Suite 503
Forest Hills, NY 11375
Telephone (718) 544-1110
Facsimile (718) 544-8588



PATENT
Attorney Docket No. JP920000287US1
Express Mail Label No. EV332925782US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

Ajith Kumar NARAYANAN

Serial No: 10/010,104

Filed: November 8, 2001

SELECTING A TARGET DEVICE IN A
DEVICE NETWORK

Examiner: LE, John H.

Art Unit: 2863

CERTIFICATE OF MAILING BY EXPRESS MAIL

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450


Dear Sir:

The undersigned hereby certifies that the attached

1. Submission of Priority Document;
2. Singapore Patent Application No. 20006973-2;
3. Return Card; and

this Certificate of Mailing by Express Mail relating to the above-referenced application were deposited as "Express Mail", Mailing Label No. EV332925782US with the U.S. Postal Service, address to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on February 12, 2005.


Dated: February 12, 2005



Mailer

Respectfully submitted,

Dated: February 12, 2005



Ido Tuchman, Reg. No. 45,924
The Law Offices of Ido Tuchman
69-60 108th Street, Suite 503
Forest Hills, NY 11375
Telephone (718) 544-1110
Facsimile (718) 544-8588

BEST AVAILABLE COPY

**REGISTRY OF PATENTS
SINGAPORE**

This is to certify that the annexed is a true copy of the following
Singapore patent application as filed in this Registry.

Date of Filing : 27 NOVEMBER 2000

Application Number : 200006973-2

Applicant(s) : INTERNATIONAL BUSINESS MACHINES
CORPORATION

Title of Invention : SELECTING A TARGET DEVICE IN A DEVICE
NETWORK

**CERTIFIED COPY OF
PRIORITY DOCUMENT**


Chig Kam Tack
CHIG KAM TACK
Assistant Registrar
for REGISTRAR OF PATENTS
SINGAPORE

SINGAPORE
THE PATENTS ACT
(CHAPTER 221)
PATENTS RULES

2 0 0 0 0 6 9 7 3 - 2
 2 7 NOV 2000

The Registrar,
 Registry of Patents.


REQUEST FOR THE GRANT OF A PATENT

THE GRANT OF A PATENT IS REQUESTED BY THE UNDERSIGNED ON THE BASIS
 OF THE PRESENT APPLICATION.

I. Title of Invention	Selecting A Target Device In A Device Network	
II. Applicant(s)	(a) Name	International Business Machines Corporation
	Body Description/ Residency	A United States company incorporated in the State of New York
	Street Name & Number	
	City	Armonk
	State	New York 10504
	Country	United States of America
	(b) Name	
	Body Description/ Residency	
	Street Name & Number	
	City	
	State	
	Country	
	(c) Name	
	Body Description/ Residency	
	Street Name & Number	

	City			
	State			
	Country			
III. Declaration of Priority	Country/Country Designated		File No.	
	Filing Date			
	Country/Country Designated		File No.	
	Filing Date			
	Country/Country Designated		File No.	
	Filing Date			
IV. Inventors				
(a) The applicant(s) is/are the sole/joint inventor(s).	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
(b) A statement on Patents Form 8 is/will be furnished.	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
V. Name of Agent	SPRUSON & FERGUSON PTE LTD			
VI. Address for Service	51 Bras Basah Road #02-03 Plaza By The Park Singapore 189554 Republic of Singapore			
VII. Claiming an earlier filing date under section 20(3), 26(6) or 47(4)	Application No			
	Filing Date			
	[Please tick in the relevant space provided]: <input type="checkbox"/> Proceeding under rule 27(1)(a). Date on which the earlier application was amended = Or <input type="checkbox"/> Proceeding under rule 27(1)(b).			
VIII. Invention has been displayed at an International Exhibition	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
IX. Section 114 requirements	The invention relates to and/or uses a micro-organism deposited for the purposes of disclosure in accordance with section 114 with a depositary authority under the Budapest Treaty. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			

2 7 NOV 2000

X. Check List	A. The application contains the following number of sheet(s):-		
	1. Request.	4	sheets
	2. Description.	13	sheets
	3. Claim(s).	4	sheets
	4. Drawing(s).	6	sheets
	5. Abstract.	1	sheets
	B. The application as filed is accompanied by:-		
	1. Priority document.	No	
	2. Translation of priority document.	No	
	3. Statement of Inventorship & right to grant.	No	
	4. International Exhibition Certificate.	No	
XI. Signature(s)	Applicant (a)	 24 NOV 2000	
	Date		
	Applicant (b)		
	Date		
	Applicant (c)		
	Date		

Agent Reference : 519908SG

NOTES:

This form when completed, shall be brought to the Registry of Patents together with the prescribed fee and 3 copies of the description of the invention, and of any drawings.

2. Enter the name and address of each applicant in the spaces provided at paragraph II. Names of individuals should be indicated in full and the surname or family name should be underlined. The names of all partners in a firm must be given in full. The place of residence of each individual should also be furnished in the space provided. Bodies corporate should be designated by their corporate name and country of incorporation and, where appropriate, the state of incorporation within that country should be entered where provided. Where more than 3 applicants are to be named, the names and address of the fourth and any further applicants should be given on a separate sheet attached to this form together with the signature of each of these further applicants.
3. The declaration of priority at paragraph III should state the date of the previous filing, the country in which it was made, and indicate the file number, if available. Where the application relied upon in an International Application or a regional patent application e.g. European patent application, one of the countries designated in that application [being one falling under the Patents (Convention Countries) Order] should be identified and the name of that country should be entered in the space provided.
4. Where the applicant or applicants is/are the sole inventor or the joint inventors, paragraph IV should be completed by marking the 'YES' Box in the declaration (a) and the 'NO' Box in the alternative statement (b). Where this is not the case, the 'NO' Box in declaration (a) should be marked and a statement will be required to be filed on Patents Form 8.
5. If the applicant has appointed an agent to act on his behalf, the agent's name should be indicated in the spaces available at paragraph V.
6. An address for service in Singapore to which all documents may be sent must be stated at paragraph VI. It is recommended that a telephone number be provided if an agent is not appointed.
7. When an application is made by virtue of section 20(3), 26(6) or 47(4), the appropriate section should be identified at paragraph VII and the number of the earlier application or any patent granted thereon identified. Applicants proceeding under section 26(6) should identify which provision in rule 27 they are proceeding under. If the applicants are proceeding under rule 27(1)(a), they should also indicate the date on which the earlier application was amended.
8. Where the applicant wishes an earlier disclosure of the invention by him at an International Exhibition to be disregarded in accordance with section 14(4)(c), then the 'YES' Box at paragraph VIII should be marked. Otherwise the 'NO' Box should be marked.
9. Where in disclosing the invention the application refers to one or more micro-organisms deposited with a depository authority under the Budapest Treaty, then the 'YES' Box at paragraph IX should be marked. Otherwise the 'NO' Box should be marked.
10. Attention is drawn to rules 90 and 105 of the Patent Rules. Where there are more than 3 applicants, see also Note 2 above.
11. Applicants resident in Singapore are reminded that if the Registry of Patents considers that an application contains information the publication of which might be prejudicial to the defence of Singapore or the safety of the public, it may prohibit or restrict its publication or communication. Any person resident in Singapore and wishing to apply for patent protection in other countries must first obtain permission from the Singapore Registry of Patents unless they have already applied for a patent for the same invention in Singapore. In the latter case, no application should be made overseas until at least 2 months after the application has been filed in Singapore.

For Official Use

Application Filing Date:

Request received on :

Fee received on :

Amount :

*Cash/Cheque/Money Order/Not:

*Delete whichever is inapplicable

SELECTING A TARGET DEVICE IN A DEVICE NETWORK

Field of the Invention

The invention is applicable to devices operating in a network environment. In particular, this invention relates to device networks, devices and a method for selecting a target device in a device network.

Background of the Invention

In a device network, devices such as printers, workstations, or mobile terminals are operably linked to process information using communication resources such as wireless channels or cables. The information includes, for example, data for processing by the devices or control signals for controlling such devices. Typically, data or control signals are provided from one or more devices to one or more other devices. Devices that receive data usually process such data based on control signals associated with the data.

Generally, devices that receive data, referred to hereinafter as "target devices", have to be selected prior to receiving and processing the data. Selection of a target device includes identifying that target device and is usually done by a user who, via a selecting device, provides one or more control signals that includes selection criteria to select the target device (e.g. a printer). The selecting device can be, for example, a hand-held mobile terminal (e.g. a Personal Digital Assistant (or PDA)) at which the user provides the selection criteria. After receiving the selection criteria, a target control signal is generated and transmitted from the selecting device to a controller for controlling the target device. In response to the target control signal, the controller sets the target device to receive the data via the communication resources, whereupon, the target device is able to be utilised.

Communicating control signals to select target devices requires communication elements such as transmitters and receivers that are either a part of the devices or are coupled to such devices. To communicate data or control signals to, for example, a printer, a user has to provide selection criteria that identify the printer. A device address, when known *apriori*, is typically used as a selection criteria. However, selection by physically pointing to the device is more natural and user friendly, and does not require knowledge of device address.

One existing technique to perform selection by physically pointing at the device is described, for example, in US Patent Number 5,963,145, issued to Escobosa on 5 October 1999. This patent describes a system having a hand held transmitter that transmits position signals at different infrared frequencies, and along divergent pointing axes, towards a device to be selected. Based on the signal strength of these position signals, a sensor coupled to the selected device determines position of the hand held transmitter. However, in the system as described in US Patent 5,963,145, interference problems are likely when more than one hand held transmitter is used at the same time. Such interference problems arise because target devices that receive the position signals have to be wide-angle sensitive (for example, due to the use of a wide-angle photo-diode), and this allows interfering signals to be received in addition to desired control signals. A second disadvantage of the system as described in US Patent 5,963,145 is that it mandates the use of IR.

In PDAs, mobile terminals and printers, provision for RF wireless communication (for example, using Bluetooth™, which is described in <http://www.bluetooth.com>) is rapidly replacing IR communication. These devices are typically fitted with omni-directional antennas. As such, in this context, directional techniques such as described in US Patent 5,963,145 are rendered useless.

Therefore, in view of the above limitations of existing techniques to select a target device, a need clearly exists for an apparatus and method for selecting the target device in a device network that is feasible in the context of non-directional wireless communication, without requiring additional support of directional communication such as IR, and is devoid of the aforementioned drawbacks of the IR based system.

Summary of the Invention

The invention discloses a device network having selectable target devices, said device network comprising:

- a controller device;

- one or more target devices in communication with said controller device; and

- one or more selecting devices, each of which is movable relative to said target devices, and includes:

 - means for sensing position and orientation to provide data therefor;

 - means for generating at least one control signal, incorporating said position

and orientation data in response to a user input; and
means for transmitting said control signals via at least one of a plurality of communication resources to said controller device; and
wherein said controller device acquires and stores actual location information for each target device, and assesses correspondence of said position and orientation data with said actual location data, and if so, outputs a control signal to select said target device to be operative.

There is further disclosed a selecting device for selecting one or more target devices in a device network, said selecting device comprising:

means for sensing position and orientation to provide data therefor;
means for generating at least one control signal, incorporating said position and orientation data, in response to a user input; and
means for transmitting said control signals via at least one of a plurality of communication resources to said controller device.

There is yet further disclosed a method for selecting one or more target devices in a device network, said method comprising the steps of:

generating a control signal from a selecting device, said control signal having position and orientation data of said selecting devices;
determining whether said one or more target devices can be identified based on said position and orientation data; and
generating a target control signal to activate an identified target device

The controller can assess correspondence from the selecting device position and orientation and the actual target location by deriving a target orientation, and determining correspondence of said target orientation with said orientation data. The orientation data can include angles between a ray joining the respective points in a three-dimensional cartesian system and two respective axes of said system. The position sensing means may comprise an accelerometer whose output is doubly integrated to give an output of position, or a positioning means using UWB. Also, the orientation sensing means can comprise a gyroscope.

Brief Description of the Drawings

Embodiments of the invention are described hereinafter with reference to the

drawings, in which:

FIG. 1 is a general block diagram of a device network having a plurality of devices in accordance with a preferred embodiment of the invention;

FIG. 2 is a general block diagram illustrating a selecting device pointing to a target device in the device network of FIG. 1;

FIG. 3 illustrates a co-ordinate system for the device network of FIG. 1;

FIG. 4 is a flowchart illustrating processing of position data by a controller of the device network of FIG. 1;

FIG. 5 is a flowchart of a method for selecting the target device in FIG. 2; and

FIG. 6 is a general block diagram of a device network in accordance with an alternate embodiment of the invention.

Detailed Description and Best Mode

Device networks, a selecting device, a target device and a method for selecting a target device in the device networks in accordance with preferred embodiments of the invention are described. In the following, numerous details are provided for a more thorough description. It shall be apparent to one skilled in the art, however, that the invention may be practised without such details. In other instances, well-known details have not been described at length so as not to obscure the invention.

Referring to FIG. 1, a general block diagram of a device network 10 having a plurality of devices in accordance with a preferred embodiment of the invention is illustrated. The plurality of devices includes four device sets 12,14,16,18 representing different types of devices of the device network 10.

The four device sets 12,14,16,18 are coupled to each other within the device network 10 via a plurality of communication resources to process signals that include control signals and data signals. Such communication resources include communication cables 20,22 and radio frequency (RF) channels 24. In FIG. 1, these communication resources 20,22,24 are labelled with alphabetic suffixes to distinguish different communication resources for each type.

The device sets 12,14 provide target devices 12a,12b,12c,14a,14b,14c such as, for example, electrical or electronic appliances. These appliances include air conditioners, television sets, stereo sound systems, photocopiers, printers or screen displays. Hence, for

an office environment in which the device network 10 is applied, a device set 14 can represent printers and a device set 12 can represent screen displays, including projection displays.

The device set 16 provides selecting devices 16a,16b,16c such as, for example, user workstations, mobile terminals, personal digital assistants (PDAs) or any hand-held devices that are movable relative to the target devices 12a,12b,12c,14a,14b,14c. In addition, the selecting devices 16a,16b,16c also allows for user input to select one or more target devices.

The device set 18 provides controllers 18a,18b that are coupled to the target devices 12a,12b,12c,14a,14b,14c and the selecting devices 16a,16b,16c via the communication cables 20,22 and the RF channels 24, respectively. These are duplex mode communications channels.

Using the selecting device 16a, the target device 12a and the controller 18a as examples, FIG. 2 illustrates one embodiment of a selecting device 16a (e.g. a hand-held unit) pointing to the target device 12a (e.g. a printer) within the device network 10.

Further illustrated in FIG. 2 is a pointing axis 32 along which the selecting device 16a is aligned when pointing to the target device 12a. The selecting device 16a is illustrated with a display 33 to provide pointing indicia, such as, for example, an arrow 34 for pointing to the target device 12a in alignment to the pointing axis 32. However, the display 33 is an optional feature that may not be necessary so long as a user can set alignment with the pointing axis 32 for the selecting device 16a.

The selecting device 16a has means for sensing position and orientation to thereby provide position and orientation data when pointing to the target device 12a, means for generating control signals including the position data, and means for transmitting the at least one control signal via the RF channel 24a. The controller 18a can be a hub or node controller, for example. The controller 18a passes data and control signals to the target device (e.g. printer) when that device is selected.

More specifically, the sensing means is in the form of a spatial sensor 26 for determining the unit's position using a co-ordinate system relative to a reference location

of the device network 10. One suitable form of sensor is a miniature accelerometer whose output (acceleration) is doubly integrated over time to obtain position. One such device is manufactured by Analog Devices of Norwood, Massachusetts, USA (www.analog.com), having part no. ADXL505. It may also be desired to reduce errors of measurement by employing a recalibration technique which takes place when a selecting device comes into proximity with a fixed (or anchor) reference device. Alternatively, or additionally, Kalman filtering techniques can be applied to overcome the effect of errors being accumulated over long periods of time. Alternatively, if the RF communication used is of the Ultra Wide Band (UWB) type, position data of high accuracy can be obtained using means specific to UWB, such as described in US Patent 6,002,708 titled Spread Spectrum Localizers, issued to Fleming and Kushner on December 14, 1999, the contents of which are incorporated herein by cross-reference. This latter method will be preferred as UWB communication gains prevalence, and has the advantage that accelerometers are not required.

The sensing means further includes an angular sensor 28 for determining the orientation of the selecting device 16a at its current position. This orientation is based on at least two angles relative to two corresponding reference axes of the device network 10. The angular sensor 28 can be, for example, an angle sensing gyroscope, or a sensor that obtains the orientation by integrating the angular rate output of an angular rate sensing gyroscope over time. An example of an angle sensing gyroscope is that identified by item no. "B99-003" from the University of California at Berkeley (<http://berkely.edu/mems.html>). Examples of suitable angular rate sensing gyroscopes are models ENC-03J and ENV-05D052, from Murata Manufacturing Co. of Japan.

The co-ordinate system that is applied in the device network 10 is illustrated by FIG. 3. As shown, three mutually orthogonal axes of the co-ordinate system correspond to, for example, an X-axis, a Y-axis and a Z-axis of a geometric Cartesian co-ordinate system. Position sensing, or positioning, establishes the position of the selecting device 16a in space, in terms of the geometric Cartesian co-ordinates (x,y,z). Orientation, or the direction in which the selecting device 16a is aligned along a pointing axis towards the target device 12a, is measured as two angles (ϕ, θ).

For convenience, this specification assumes the use of (x,y,z) and (ϕ, θ) to represent the position and the orientation of a device 12,14,16, respectively. Other

equivalent co-ordinate systems, though not described, can be applied in the embodiments of this invention since co-ordinates and angles in one co-ordinate system can be used to compute corresponding co-ordinates and angles in such other equivalent co-ordinate systems.

The choice of the origin (0,0,0) is unimportant, since distances measured using the co-ordinate system applied in the embodiments of this invention are relative distances. The choice of the mutually orthogonal axes is also unimportant. Generally, but not necessarily so, the Z-axis is aligned to the gravitational "up" direction. Consequently, this allows the the X-axis or the Y-axis to align with the magnetic meridian of the Earth at some chosen point, thus providing a convenient definition of all three axes. Any other definition may equally well be used, as long as a consistent use is guaranteed. It is necessary that all devices 12,14,16 that participate in the described computation refer to the same co-ordinate system and axes of reference for consistency.

Referring once again to FIG. 3, the selecting device 16a is positioned at point P with co-ordinates (x_1, y_1, z_1) and (ϕ_1, θ_1) to denote, respectively, the position and the orientation of the selecting device 16a. Let (x_2, y_2, z_2) denote the co-ordinates of the target device 12a, which is at the position represented by point Q. X' , Y' and Z' are parallels to the X, Y, Z axes such that they pass through point P. Accordingly, Q' is the projection of Q on the $X'Y'$ plane. Then, ϕ_1 is the angle between the X axis and PQ' . θ_1 is the angle between the Z axis and the vector PQ. N and M are projections of Q on the X' and Z' axes respectively, as in FIG. 3.

From an analysis of triangle $PQ'N$,

$$\tan(\phi_1) = Q'N / PN = (y_2 - y_1) / (x_2 - x_1) \quad \text{--} \quad \text{(Equation 1),}$$

and from triangle PQM,

$$\cos(\theta_1) = PM / PQ = (z_2 - z_1) / d \quad \text{--} \quad \text{(Equation 2),}$$

where $d = PQ$, which is the distance between the selecting device 16a at point P and the target device 12a at point Q.

Equation 1 and Equation 2 provide for the determining of the position and the orientation of the selecting device 16a and the position of the target device 12a in the embodiments of this invention. Clearly, the target device's position also must be known in terms of (x_2, y_2, z_2) .

The generating means of the selecting device 16a comprises a signal processor 29 for processing the position and orientation data, provided as co-ordinates, that are based on the co-ordinate system described in the above. The signal processor incorporates the position and orientation data into a control signal. Thereafter, the transmitting means, comprising a transmitter 31, transmit the control signal via the RF channel 24a to the controller 18a. An example of the transmitting means is a Bluetooth™ RF wireless communication interface. The control signal may be encoded, for example, as a message packet containing the position and orientation data, which is communicated over a Bluetooth™ connection.

The selecting device 16a further comprises a user input means 30 that can be, for example, a keypad. The input means 30, coupled to the signal processor 29, enables a user to provide user inputs to activate the signal processor 29 to determine the position and the orientation of the selecting device 16a.

The target device 12a comprises an interface 35 for receiving, via the communication cable 22a, data signals and control signals from the controller 18a. Such an interface 35 includes communications elements that are generally known in the art. In addition, the target device 12a further comprises a signal processor 36, coupled to the interface 35, for processing control signals having embedded position data. Such control signals include target control signals received from the controller 18a that provides the necessary reference position data.

The processing steps 40, illustrated in the flowchart of FIG. 4, describe the method by which controller (e.g. 18a) determines whether a target device (e.g. 12a) is selected or not, based on the position and orientation data of the selecting device (e.g.) 16a, and the position data of the target device (e.g. 12a). Processing of these position and orientation data is as illustrated in the flowchart of FIG. 4.

The processing 40 starts at step 41 in which the position co-ordinates (x_1, y_1, z_1)

and the orientation co-ordinates (ϕ_1, θ_1) of the selecting device 16a are obtained from the control signal transmitted from the selecting device 16a. Following step 41, the processing 40 continues to step 42 to obtain the known position co-ordinates (x_2, y_2, z_2) of the target device 12a. The controller 18a then computes the angle ϕ at step 43 using:

$$\phi = \tan^{-1} \{(y_2 - y_1) / (x_2 - x_1)\},$$

Following the computation of ϕ , the processing 40 continues to decision step 44 in which the controller 18a determines whether ϕ is in the neighborhood of ϕ_1 , i.e., in the range $(\phi_1 - \delta \phi, \phi_1 + \delta \phi)$ where $\delta \phi$ is a suitably chosen angular window.

The value of $\delta \phi$ may be computed based on the angle subtended by the breadth of the target device at the selector, and the accuracy of orientation required for selection to occur. For example, $\delta \phi = k \cdot \frac{1}{2} \cdot \tan^{-1} (w / PQ)$ where w is the breadth of the target facing the selector, and k is a constant whose nominal value is 1, and may be increased or decreased to widen or narrow the window of selection.

With a "Yes" following decision step 44, the processing 40 continues to step 45. At step 45, the angle θ is computed using:

$$\theta = \cos^{-1}(z_2 - z_1 / d),$$

where d = distance between P and Q

$$= \sqrt{\{(x_2 - x_1)^2 + (y_2 - y_1)^2 + (z_2 - z_1)^2\}}.$$

Otherwise, with a "No" following decision step 44, the processing 40 stops at end step 46 and the target device 12a is therefore not selected.

At decision step 47, upon computation of the angle θ , the controller determines whether θ is in the range $(\theta_1 - \delta \theta, \theta_1 + \delta \theta)$ where $\delta \theta$ is a suitably chosen angular window.

The value of $\delta \theta$ may be computed based on the angle subtended by the height of the target device at the selector, and the accuracy of orientation required for selection to occur. For example, $\delta \theta = k \cdot \frac{1}{2} \cdot \tan^{-1} (h / PQ)$ where h is the height of the target facing the selector, and k is a constant whose nominal value is 1, and may be increased or

decreased to widen or narrow the window of selection.

With a "Yes" following decision step 47, the processing 40 continues to step 48 at which the target device 12a is selected. Otherwise, the processing 40 does not select the target device 12a and, with a "No", stops at end step 46.

Referring now to FIG. 5, a method 50 for selecting one or more target devices in the device network 10 is illustrated with a flowchart. Using the target device 12a, the selecting device 16a and the controller 18a shown in FIG. 2, the method begins at step 51 and proceeds to step 52 in which the controller 18a receives at least one control signal from the selecting device 16a. The control signal has the position data of the selecting device, for example 16a, when the selecting device 16a is pointing to the target device, for example, 12a.

Thereafter, the method 50 proceeds to step 53 at which the controller 18a processes the position and orientation data to determine the position and the orientation of the selecting device 16a relative to the target device 12a. Continuing on to decision step 54, the controller 18a determines whether the target device 12a can be identified based on the position data provided by the control signal, using the above-described method 40.

Upon a 'Yes' result following decision step 54, the method 50 proceeds to step 54. In step 54, the controller 18a generates at least one target control signal to activate the target device 12a to process data signals provided in association with the control signal from the selecting device 16a when determined that the position data is sufficient to identify the target device 12a.

Otherwise, upon a 'No' result following decision step 54, the method 50 ends, and the target device 12a is not selected. Such a situation may occur when, for example, the pointing axis 32 of the selecting device 16a is not appropriately or sufficiently aligned towards the target device 12a.

The method 50 describes selection of a single target device 12a from the device set 12. However, when the pointing axis 32 may be determined to be pointing towards more than one target device in the device set 12, e.g., due to target devices being too closely located and/or angular windows $\delta\phi$, $\delta\theta$ being too wide to allow for discrimination,

or for any other reasons. In such cases, different selection criteria may be applied to discriminate and narrow the selection, in conjunction with method 50 as described. For example, one of the selection criteria is to use *distance* to identify a desired target device which is closest to the selecting device, when the targets are collinear with the selector. Alternatively, another selection criteria is to use *attribute matching* such as, for example, choosing the least used target device from the device set 12. A further selection criteria is to have the user select the target device 12a interactively via a display menu viewable on the display 33. Yet a further selection criteria is to have a user or an administrator of the target device 12a determine whether to process the at least one target control signal and determine whether to enable selection of the target device 12a. These methods can be combined with the above-described method 50 to narrow the selection, as follows.

For example, when device set 12 is a set of printers, a load balancing criteria may be applied such that controller 18a keeps track of the service load of each printer, and deems the least loaded printer as the selected target. Alternatively, controller 18a may send a control signal back to selecting device 16a, incorporating a list of the one or more targets (say 12b,12c) that are eligible for selection, optionally accompanied by their descriptions. Then, device 16a displays this list to the user on the display 33, allowing an interactive selection to be performed by the user, the resulting choice (e.g. 12c) being transmitted to controller 18a in the form of a control signal, whereby controller 18a selects the chosen target (12c).

It is also possible to select more than one target device from either the device set 12 or the device set 14 depending on how the signal processor 29 processes the one or more control signals and the user inputs. For example, the user, by keeping the user input means 30 activated, places the selecting device 16a in a scanning mode. In the scanning mode, a sweeping motion is made with the selecting device 16a to select more than one target device from the device set 12 or the device set 14. The processing 40 and the method 40 is then activated in succession for the target devices 12a,12b,12c,14a,14b,14c are then sequentially selected.

A schematic block diagram shown in FIG. 6 illustrates a device network 60 in accordance with an alternate embodiment of the invention. In the device network 60, the communication resources coupling the controllers 18a,18b to the target devices 12a,12b,12c in the device set 12 are RF or IR channels 61a,61b. Hence, the device

network 60 represents a wireless device network in which signals, such as control signals and data signals, are communicated via RF or IR channels 24a,24b,61a,61b.

Yet another alternate embodiment of the invention employs target devices (e.g. 12,14) that are computationally inactive; for example, pictures hanging on a wall or shelves in a supermarket. Instead, their position data is stored in the controller 18a, and thus communication resources 20,22 are not necessary in this embodiment. The act of selection of a target, e.g. 12a, is determined by the controller 18a using method 50 and 40 as previously described. The selection of a target causes an action to be performed by the controller, which, in this case, depends on the identity of the selected target but, in contrast to the embodiments discussed previously, does not involve communication with the selected target. For example, targets 12a,12b,12c,12d may be paintings hanging on a wall, such that the selection of a target, 12a, causes controller 18a to, for example, send a control signal to the selecting device 16a, incorporating information relating to the painting 12a, which is then displayed on display 33 of device 16a. Likewise, in a supermarket browsing application, information about the items on the shelf may be presented on the display when the shelf is selected by pointing to.

The advantages of the preferred embodiments of the invention are manifold. One advantage of the preferred embodiments of the invention becomes apparent as selecting devices, e.g. PDAs, are increasingly equipped with RF communication, e.g. using Bluetooth. The invention disclosed here permits such selecting devices, that are capable of wireless communication, with no added hardware such as IR, to perform target selection. This means that the selection functionality is implementable purely in software and on top of off-shelf hardware, which is cost-effective.

Yet a further advantage of the preferred embodiments of the invention is that selecting a target device does not require directional communication resources such as infrared channels. Hence, inherent problems such as signal interferences from other devices using such directional communication resources and operating in the same device network are not encountered in the device networks of the invention.

A third advantage of the embodiment involving computationally inactive targets, for example, supermarket shelves, is that no communication hardware need to be installed for every such target, resulting in tremendous savings of hardware cost when compared to

existing techniques.

Another embodiment of the invention operates on the principle of determining only one angle of a orientation. In other words, a 'plane of orientation' is determined rather than a 'pointing line'. This is less desirable, however, as unwanted objects may be in the plane and be selected. Some degree of filtering would be required, as discussed above with respect to 'narrowing the selection'.

In the foregoing description, device networks, a selecting device, a target device and a method for selecting a target device in the device networks in accordance with preferred embodiments of the invention are described. Although preferred embodiments are described, it shall be apparent to one skilled in the art in view of these preferred embodiments that numerous changes and/or modifications can be made without departing from the scope and spirit of the invention.

I claim:

- I. A device network having selectable target devices, said device network comprising:
 - a controller device;
 - one or more target devices in communication with said controller device; and
 - one or more selecting devices, each of which is movable relative to said target devices, and includes:
 - means for sensing position and orientation to provide data therefor;
 - means for generating at least one control signal, incorporating said position and orientation data in response to a user input; and
 - means for transmitting said control signals via at least one of a plurality of communication resources to said controller device; andwherein said controller device acquires and stores actual location information for each target device, and assesses correspondence of said position and orientation data with said actual location data, and if so, outputs a control signal to select said target device to be operative.
2. The device of claim 1, wherein said controller assesses correspondence from the selecting device position and orientation and said actual target location by deriving a target orientation, and determining correspondence of said target orientation with said orientation data.
3. The device of claim 1, wherein said orientation data includes angles between a ray joining the respective points in a three-dimensional cartesian system and two respective axes of said system.
4. The device network of claim 2, wherein said position sensing means comprises an accelerometer whose output is doubly integrated to give an output of position, or a positioning means using UWB.
5. The device network of claim 4, wherein said orientation sensing means comprises a gyroscope.

6. The device of claim 5, wherein said each selecting device includes a pointing means to line up a said target device.
7. The device network of claim 6, wherein said pointing means is a display, printed indicium, or pointed shape.
8. The device network of claim 1, wherein communication between said selecting devices and said controller device is wireless.
9. The device network of claim 8, wherein said wireless communication is either RF or IR types.
10. The device of claim 1, wherein communication between said target devices and said controller device is wired or wireless.
11. A selecting device for selecting one or more target devices in a device network, said selecting device comprising:
 - means for sensing position and orientation to provide data therefor;
 - means for generating at least one control signal, incorporating said position and orientation data, in response to a user input; and
 - means for transmitting said control signals via at least one of a plurality of communication resources to said controller device.
12. The selecting device of claim 11, wherein said position sensing means comprises an accelerometer whose output is doubly integrated to give an output of position, or a positioning means using UWB.
13. The selecting device of claim 12, wherein said orientation sensing means comprises a gyroscope.
14. The selecting device of claim 13, wherein said each selecting device includes a pointing means to line up a said target device.
15. The selecting device of claim 11, wherein said transmitting means is wireless.

16. The selecting device of claim 15, wherein wireless communication is either IR or RF types.

17. A method for selecting one or more target devices in a device network, said method comprising the steps of:

generating a control signal from a selecting device, said control signal having position and orientation data of said selecting devices;

determining whether said one or more target devices can be identified based on said position and orientation data; and

generating a target control signal to activate an identified target device.

18. The method of claim 17, wherein said determining step is performed by deriving a target orientation from the selecting device location and actual target location, and comparing said derived orientation with said orientation data.

19. A method for selecting a target, said method comprising the steps of:

generating a control signal from a selecting device, said control signal having position and orientation data of said selecting devices; and

determining whether a target of known location can be identified based on said position and orientation data.

20. The method of claim 19, wherein said determining step is performed by deriving a target orientation from the selecting device location and actual target location, and comparing said derived orientation with said orientation data.

21. A device network having selectable target devices, said device network comprising:

a controller device;

one or more targets; and

one or more selecting devices, each of which is movable relative to said targets,

and includes:

means for sensing position and orientation to provide data therefor;

means for generating at least one control signal, incorporating said position

and orientation data in response to a user input; and

means for transmitting said control signals via at least one of a plurality of communication resources to said controller device; and

wherein said controller device stores actual location information for each target, and assesses correspondence of said position and orientation data with said actual location data, and if so, selects said target.


22. The device of claim 21, wherein said controller assesses correspondence from the selecting device position and orientation and said actual target location by deriving a target orientation, and determining correspondence of said target orientation with said orientation data.

SELECTING A TARGET DEVICE IN A DEVICE NETWORK

ABSTRACT

A device network (10) to process signals has target devices (12, 14), selecting devices (16) that are movable relative to the target devices (12, 14), and controllers (18). The controllers (18) are in communication with the target devices (12, 14) and the selecting devices (16). Each of the selecting devices (16) has a position sensor and an orientation sensor to provide spatial and angular co-ordinates of position and orientation when pointing to a target device (12 or 14) and upon receiving a user input. Each of the selecting devices (16) also has a signal processor to generate a control signal having the position and orientation data. This control signal is then transmitted by a transmitter, via a radio frequency channel (24a), to a controller (18a). Upon receiving the control signal, the controller (18a) determines whether, for example, a target device (12a) has been selected by a selecting device (16a) by comparison of the orientation data with a derived orientation based on the position data and the known position of the target devices.

FIG 2







FIG. 2

*FIG. 3*




FIG. 4





FIG. 5

*FIG. 6*

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.